

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) A method of controlling transmission power in a mobile radio system in which a power control algorithm controls transmission power as a function of a transmission quality target value, ~~wherein~~ said method comprising the steps of:

varying a target value ~~variation is applied~~ to compensate the effects of a compressed transmission mode in which transmission is interrupted during transmission gaps and the bit rate is increased correspondingly to compensate the transmission gaps, said target value variation ~~includes~~ including a first component for compensating the effects of said ~~increase in~~ increased bit rate and a second component for compensating other effects of transmission gaps, and

anticipatorily varying a corresponding anticipated variation of the transmission power by an amount corresponding is applied, and said anticipated variation of the transmission power corresponds to an approximate value of said target value variation obtained by a process of approximation from said second component.

2. (Original) A method according to claim 1, wherein an approximate value of said second component for a given transmission direction is obtained from the second component for the opposite transmission direction.

3. (Original) A method according to claim 1, wherein:

said power control algorithm simultaneously controls the transmission power of at least two channels, including a data channel and a control channel, as a function of a transmission quality target value,

the transmission power of said control channel is offset relative to the transmission power of said data channel, and

in the event of target value variation, anticipated variations of the transmission power of the data channel and/or the transmission power of the control channel and/or the offset of the transmission power of the control channel relative to the transmission power of the data channel are applied in order to obtain an anticipated variation of the transmission power of the data channel that corresponds to said approximate value of the target value variation.

4. (Original) A method according to claim 3, wherein, in the event of target value variation, said anticipated variations of the transmission power of the data channel and/or of the transmission power of the control channel and/or of the offset of transmission power of the control channel relative to the transmission power of the data channel are determined so that the power of the signal transmitted on the control channel is the same before and after said target value variation and over the same reference period.

5. (Original) A method according to claim 3, wherein, in the event of target value variation, an anticipated variation of the offset of the transmission power of the control channel

relative to the transmission power of the data channel is applied that corresponds to the opposite of said approximate value of the target value variation.

6. (Original) A method according to claim 3, wherein, in the event of target value variation, an anticipated variation of the transmission power of the data channel and the transmission power of the control channel is applied that corresponds to said approximate value of the target value variation.

7. (Original) A method according to claim 1, wherein said target value is adjusted by an adjustment algorithm as a function of a required quality of service and said target value variation is intended, in the event of a change to the required quality of service, to anticipate the corresponding target value variation adjusted by said adjustment algorithm.

8. (currently amended) A mobile radio system which practices a transmission power control method in which a power control algorithm controls transmission power as a function of a transmission quality target value, said transmission power control method comprising the steps of: varying a target value to compensate the effects of a compressed transmission mode in which transmission is interrupted during transmission gaps and the bit rate is increased correspondingly to compensate the transmission gaps, said target value variation including a first component for compensating the effects of said increased bit rate and a second component for compensating other effects of transmission gaps; and anticipatorily varying the transmission power by an

amount corresponding to an approximate value of said target value variation obtained by a process of approximation from said second component, said mobile radio system including, for implementing a method according to claim 1, means for applying, in the event of target value variation, an said anticipated anticipatory variation of the transmission power that corresponds to said approximate value of the target value variation.

9. (currently amended) A mobile radio system according to claim 8, wherein said transmission power control algorithm simultaneously controls the transmission power of at least two channels, including a data channel and a control channel, as a function of transmission quality target value, with the transmission power of said control channel offset relative to the transmission power of said data channel, and wherein, in the event of target value variation, anticipated variations of at least one of the transmission power of the data channel, the transmission power of the control channel and the offset of the transmission power of the control channel relative to the transmission power of the data channel are applied in order to obtain said anticipatory variation of the transmission power of the data channel, said mobile radio system including, for implementing a method according to claim 3, means for applying, in the event of target value variation, anticipated variations of at least one of the transmission power of the data channel, and/or the transmission power of the control channel and/or the offset of the transmission power of the control channel relative to the transmission power of data channel to obtain an said anticipated anticipatory variation of the transmission power of the data channel that corresponds to said approximate value of the target value variation.

10. (currently amended) A mobile radio system according to claim 9, further including means such that, in the event of target value variation, said anticipated variations of the at least one of the transmission power of the data channel, ~~and/or~~ the transmission power of the control channel and/or the offset of the transmission power of the control channel relative to the transmission power of the data channel cause the signal transmitted on the control channel to have the same power before and after said target value variation and over the same reference period.

11. (currently amended) A mobile radio system according to claim 8, including means for applying, in the event of target value variation, an anticipated variation of the offset of the transmission power of the control channel relative to the transmission power of the data channel that corresponds to the opposite of said approximate value of the target value variation.

12. (currently amended) A mobile radio system according to claim 8, including means for applying, in the event of target value variation, an anticipated variation of the transmission power of said data channel and the transmission power of said control channel that corresponds to said approximate value of the target value variation.

13. (currently amended) A base station for use in a mobile radio system which practices a transmission power control method in which a power control algorithm controls a downlink

transmission power as a function of a transmission quality target value, said transmission power control method comprising the steps of: varying a target value to compensate the effects of a compressed transmission mode in which transmission is interrupted during transmission gaps and the bit rate is increased correspondingly to compensate the transmission gaps, said target value variation including a first component for compensating the effects of said increased bit rate and a second component for compensating other effects of transmission gaps; and anticipatorily varying the transmission power by an amount corresponding to an approximate value of said target value variation obtained by a process of approximation from said second component, said base station including, for implementing a downlink power control method according to claim 1, means for applying, in the event of target value variation, an anticipated variation of the transmission power that corresponds to said approximate value of the target value variation said anticipatory variation of said transmission power.

14. (currently amended) A base station for use in a mobile radio system which practices a transmission power control method in which a power control algorithm controls downlink transmission power as a function of a transmission quality target value, said transmission power control method comprising the steps of: varying a target value to compensate the effects of a compressed transmission mode in which transmission is interrupted during transmission gaps and the bit rate is increased correspondingly to compensate the transmission gaps, said target value variation including a first component for compensating the effects of said increased bit rate and a second component for compensating other effects of transmission gaps; and anticipatorily

varying the transmission power by an amount corresponding to an approximate value of said target value variation obtained by a process of approximation from said second component,
wherein said transmission power control algorithm simultaneously controls the transmission power of at least two channels, including a data channel and a control channel, as a function of transmission quality target value, with the transmission power of said control channel offset relative to the transmission power of said data channel, said mobile radio system including,~~for implementing a downlink power control method according to claim 3,~~ means for applying, in the event of target value variation, anticipated variations of at least one of the transmission power of the data channel, ~~and/or~~ the transmission power of the control channel ~~and/or~~ the offset of the transmission power of the control channel relative to the transmission power of the data channel, to obtain ~~an anticipated~~ said anticipatory variation of the transmission power of the data channel that corresponds to said approximate value of the target value variation.

15. (currently amended) A base station according to claim 14, further including means such that, in the event of target value variation, said ~~anticipated~~ anticipatory variations ~~of the transmission power of the data channel and/or the transmission power of the control channel and/or the offset of the transmission power of the control channel relative to the transmission power of the data channel~~ cause the signal transmitted on the control channel to have the same power before and after said target value variation and over the same reference period.

16. (currently amended) A base station according to claim 13, including means for applying an ~~anticipated~~anticipatory variation of the offset of the transmission power of the control channel relative to the transmission power of the data channel that corresponds to the opposite of said approximate value of the target value variation.

17. (currently amended) A base station according to claim 13, including means for applying an ~~anticipated~~anticipatory variation of the transmission power of said data channel and the transmission power of said control channel that corresponds to said approximate value of the target value variation.

18. (Original) A base station according to claim 13, including means for using said second component which is signaled to it by a base station controller for the purposes of uplink power control to determine said approximate value of the downlink target value variation.

19. (currently amended) A mobile station for use in a mobile radio system which practices a transmission power control method in which a power control algorithm controls transmission power as a function of a transmission quality target value, said transmission power control method comprising the steps of: varying a target value to compensate the effects of a compressed transmission mode in which transmission is interrupted during transmission gaps and the bit rate is increased correspondingly to compensate the transmission gaps, said target value variation including a first component for compensating the effects of said increased bit rate

and a second component for compensating other effects of transmission gaps; and anticipatorily varying the transmission power by an amount corresponding to an approximate value of said target value variation obtained by a process of approximation from said second component, said mobile station including, for implementing an uplink power control method according to claim 1, means for applying, in the event of target value variation, an anticipated said anticipatory variation of the to an uplink transmission power that corresponds to said approximate value of the target value variation.

20. (currently amended) A mobile station for use in a mobile radio system which practices a transmission power control method in which a power control algorithm controls uplink transmission power as a function of a transmission quality target value, said transmission power control method comprising the steps of: varying a target value to compensate the effects of a compressed transmission mode in which transmission is interrupted during transmission gaps and the bit rate is increased correspondingly to compensate the transmission gaps, said target value variation including a first component for compensating the effects of said increased bit rate and a second component for compensating other effects of transmission gaps; and anticipatorily varying the transmission power by an amount corresponding to an approximate value of said target value variation obtained by a process of approximation from said second component, wherein said transmission power control algorithm simultaneously controls the transmission power of at least two channels, including a data channel and a control channel, as a function of transmission quality target value, with the transmission power of said control channel

offset relative to the transmission power of said data channel, said mobile radio system
including, ~~for implementing an uplink power control method according to claim 3,~~ means for
applying, in the event of target value variation, anticipated variations of at least one of the
transmission power of the data channel, ~~and/or the transmission power of the control channel~~
~~and/or the offset of the transmission power of the control channel relative to the transmission~~
power of the data channel, to obtain an anticipated variation of the data channel transmission
power ~~that corresponds to said approximate value of the target value variation.~~

21. (currently amended) A mobile station according to claim 20, further including means
such that in the event of target value variation said anticipated variations ~~of the transmission~~
~~power of the data channel and/or the transmission power of the control channel and/or the offset~~
~~of the transmission power of the control channel relative to the transmission power of the data~~
~~channel~~ cause the signal transmitted on the control channel to have the same power before and
after said target variation and over the same reference period.

22. (Original) A mobile station according to claim 20, further including means for
applying an anticipated variation of the offset of the transmission power of the control channel
relative to the transmission power of the data channel that corresponds to the opposite of said
approximate value of the target value variation.

23. (Original) A mobile station according to claim 20, further including means for applying an anticipated variation of the transmission power of said data channel and the transmission power of said control channel that corresponds to said approximate value of the target value variation.

24. (Original) A mobile station according to claim 19, further including means for using said second component which is signaled to it by a base station controller for the purposes of uplink power control to determine said approximate value of the downlink target value variation.

25. (currently amended) A base station controller for use in a mobile radio system which practices a transmission power control method in which a power control algorithm controls transmission power as a function of a transmission quality target value, said transmission power control method comprising the steps of: varying a target value to compensate the effects of a compressed transmission mode in which transmission is interrupted during transmission gaps and the bit rate is increased correspondingly to compensate the transmission gaps, said target value variation including a first component for compensating the effects of said increased bit rate and a second component for compensating other effects of transmission gaps; and anticipatorily varying the transmission power by an amount corresponding to an approximate value of said target value variation obtained by a process of approximation from said second component, said base station controller including, ~~for implementing the method according to claim 1,~~ means for

Amendment
USSN 09/878,269

signaling the same value for said second component for both transmission directions to a base station and to a mobile station.